



# Electrolux

## Digital Cabinets Benefit - 1 Full Door Digital Freezer - 600 lt

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



790133 (SB600F1D3C)

Benefit Digital 1 Full Door  
Freezer - 600 lt - 230  
V/1N/50Hz

### Short Form Specification

#### Item No.

Fully constructed in 304 AISI stainless steel. High-density expanded polyurethane insulating foam, 60mm in thickness. Lockable door with closure latch and microswitch to switch off the fan when the door is opened. Built-in refrigeration unit; ventilated operating mode; digital control; automatic defrost and evaporation of defrost water; external digital temperature display. Air conveyors allow installation up to 2100 mm from ceiling. For ambient temperatures up to 43 °C. CFC and HCFC free. R404a gas in refrigeration circuit. Mounted on 85 mm feet, adjustable in height up to 125 mm.

Supplied with n. 3x2/1GN nylon coated grids and n. 3 sets of 2 stainless steel grid runners.

### Main Features

- IP65 digital control panel allows for temperature and parameter setting as well as to activate defrosting when necessary.
- Equipped with air conveyors to allow cabinet installation even up to 2100 mm of distance from ceiling.
- The digital control features service and HACCP alarms and can be connected to a remote computer.
- Freezer model has operating temperatures that can be adjusted from -22 to -15 °C.
- Forced air circulation for rapid cooling and an even temperature distribution.
- Large storage area suitable to contain 2/1 GN grids or shelves on anti-tilt runners.
- Lockable door with closure latch.
- Automatic evaporation of defrost water.
- Door frame heater, activated according to external temperature, avoids condensation build-up around the door frame.

### Construction

- Mounted on 85 mm feet, adjustable in height up to 125 mm.
- Electronic protection against high voltage peaks.
- Coated evaporator to avoid corrosion and to guarantee everlasting operation.
- Easy to clean, reversible self-closing door with baloon profile, magnetic door seal to guarantee perfect closure.
- The rounded internal corners, the easily removable runners and grids allow for ease of cleaning and high hygiene standards.
- High density polyurethane insulation, 60 mm thickness, HCFC free.
- CFC and HCFC-free insulation.
- Refrigerant type: R404a.
- Built-in compressor to suit operating conditions.
- Stainless steel AISI 304 internal and external panels including back.

### Included Accessories

- 3 of Kit of 1x2/1GN PVC grids with side runners for 600/1300lt refrigerated cabinets PNC 880297

### Optional Accessories

- Kit of 4 low feet for cabinets PNC 880264
- Kit of 1x2/1GN PVC grids with side runners for 600/1300lt refrigerated cabinets PNC 880297

APPROVAL: \_\_\_\_\_



Experience the Excellence  
[www.professional.electrolux.com](http://www.professional.electrolux.com)  
[professional@electrolux.com](mailto:professional@electrolux.com)



Electrolux

Benefit - 1 Full Door Digital Freezer - 600 lt  
Digital Cabinets



**Electrolux**

**Digital Cabinets  
Benefit - 1 Full Door Digital Freezer  
- 600 lt**

- Kit of 5 wheels (front with brake) for cabinets and counters PNC 880301




**Digital Cabinets  
Benefit - 1 Full Door Digital Freezer - 600 lt**


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2019.07.10

Front




Side



EI = Electrical inlet (power)  
 RI = Refrigerant Inlet  
 RO = Refrigerant Outlet

Top



### Electric

Supply voltage:  
 790133 (SB600F1D3C) 220-230 V/1 ph/50 Hz

### Key Information:

Gross capacity: 600 lt  
 Door hinges:  
 External dimensions, Width: 720 mm  
 External dimensions, Height: 1985 mm  
 External dimensions, Depth: 780 mm  
 External dimensions, Depth with Doors Open: 1450 mm  
 Number and type of doors: 1 Full  
 Number and type of grids (included): 3 - GN 2/1  
 Type of external material: Stainless Steel AISI 304 Scotch Brite  
 Type of internal material: Stainless Steel AISI 304 Scotch Brite  
 Number of positions & pitch: 40; 30 mm

### Refrigeration Data

Refrigerant type: R404A  
 Operating temperature min.: -22 °C  
 Operating temperature max.: -15 °C  
 Operating mode: Ventilated  
 Cooling unit: Built-In  
 Defrost type: Electric